# **MATERIAL SAFETY DATA SHEET**

AGFA CORPORATION 100 Challenger Road Ridgefield Park, NJ 07660

TRANSPORTATION EMERGENCYNON-TRANSPORTATIONCALL CHEMTREC:800-424-9300HEALTH EMERGENCY PHONE..: (303) 623-5716INTERNATIONAL:703-527-3887AGFA INFORMATION PHONE..: (201) 440-2500

# 1. CHEMICAL PRODUCT IDENTIFICATION:

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS:

INGREDIENT NAME /CAS NUMBER EXPOSURE LIMITS CONCENTRATION (%) \_\_\_\_\_ \_\_\_\_\_ \*\*\*\*\* HAZARDOUS INGREDIENTS \_\_\_\_\_ Acetic Acid 64-19-7 OSHA PEL: 10 ppm TWA 25 mg/m3 ACGIH TLV: 10 ppm TWA 25 mg/m3 1-5 % Aluminum Sulfate 10043-01-3 OSHA PEL : Not Established 1-5 % ACGIH TLV: 2.0 mg/m3 TWA\* \*Aluminum, Soluble Salts (as Al) Nonylphenol polyethylene oxide 9016-45-9 OSHA PEL : Not Established 1-5 % ACGIH TLV: Not Established

## 3. HAZARDS IDENTIFICATION:

This product as a whole has not been tested. This hazard information is for the individual ingredients.

#### POTENTIAL HEALTH EFFECTS:

ROUTE(S) OF ENTRY...... Eye and skin contact, inhalation of vapors or mists, accidental ingestion. HUMAN EFFECTS AND SYMPTOMS OF OVEREXPOSURE:

- ACUTE INHALATION...........: Overexposure to acetic acid vapors and aluminum sulfate can cause irritation to the respiratory tract resulting in coughing, runny nose and sore throat. Inhalation of nonylphenol polyethylene oxide may be irritating to the mucous membranes of the respiratory tract with symptoms of coughing, sore throat, and runny nose.
- ACUTE SKIN CONTACT......: Direct contact with acetic acid and aluminum sulfate can cause skin irritation with symptoms of burning, reddening, itching, and swelling. Skin sensitization with acetic acid is rare, but has been reported. Direct contact with the nonylphenol polyethylene oxide may cause irritation resulting in reddening, itching, drying and stinging.
- ACUTE EYE CONTACT......: Overexposure to acetic acid can cause severe irritation resulting in burning, stinging, reddening, tearing, swelling and possible injury to the cornea depending on the concentration of the acid. Aluminum sulfate may cause irritation and possible corneal burns due to the reaction of the compound with moisture to form sulfuric acid. Direct contact with nonylphenol polyethylene oxide may cause irritation resulting in reddening, itching, drying and stinging.
- ACUTE INGESTION......: Swallowing concentrated acetic acid may cause severe injury. Ingestion of aluminum sulfate may cause irritation or burn the digestive tract.
- CHRONIC EFFECTS OF EXPOSURE...: No applicable information was found concerning any adverse chronic health effects from overexposure to this product.
- CARCINOGENICITY.....: The components of this product are not listed by NTP, IARC or regulated as a carcinogen by OSHA.

#### MEDICAL CONDITIONS

AGGRAVATED BY EXPOSURE.....: Persons with preexisting eye, skin or respiratory tract disorders may be more susceptible to the effects of this product.

#### 4. FIRST AID MEASURES:

FIRST AID FOR EYES.....: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

FIRST AID FOR SKIN.....: Flush affected areas promptly with water and soap for 15 minutes. Remove contaminated clothing. In case of continued irritation consult physician.

FIRST AID FOR INHALATION: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

FIRST AID FOR INGESTION.: If swallowed, rinse mouth with plenty of water, call a Physician.

#### 5. FIRE FIGHTING MEASURES:

FLASH POINT..... Noncombustible

EXTINGUISHING MEDIA...... Material is not combustible. Use extinguishing media suitable for other combustible materials in the area.

SPECIAL FIRE FIGHTING PROCEDURES: Evacuate personnel to a safe area. Keep personnel removed and upwind of fire. Wear self-contained breathing apparatus.

UNUSUAL FIRE / EXPLOSION HAZARDS: When heated to decomposition emission of toxic fumes of SO2 is possible.

# 6. ACCIDENTAL RELEASE MEASURES:

SPILL OR LEAK PROCEDURES...... Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean up. Dike Spill. Prevent liquid from entering sewers, waterways or low areas. Soak up with sawdust, sand, oil dry or other absorbent material. Spill may be neutralized with powdered Sodium Carbonate. For disposal see section 13.

## 7. HANDLING AND STORAGE:

HANDLING/STORAGE PRECAUTIONS: Avoid eye and skin contact, and store in well-ventilated area. Keep container tightly closed. Do not store with incompatible materials. Do not store or consume food, drink or tobacco in area where they may become contaminated with this material. For incompatibles see section 10. OTHER NOTES...... Keep out of the reach of children.

## 8. PERSONAL PROTECTION:

PROTECTIVE CLOTHING REQUIREMENTS...: Splash protection required for eyes, e.g., eye glasses with side shields or goggles. For skin protection use chemical resistant gloves and aprons, e.g. made of neoprene, rubber or vinyl.

VENTILATION REQUIREMENTS.....: Use sufficient general room ventilation and/or local exhaust to maintain airborne levels of vapors below applicable exposure limits (see Section 2).

RESPIRATOR REQUIREMENTS.....: Under normal conditions of use, respirator protection is not required. If respirators are used, institute a program in accordance with OSHA standard 29CFR1010.134.

ADDITIONAL PROTECTIVE MEASURES.....: Emergency showers and eye wash stations should be made available. Educate and train employees in the safe use and handling of this product.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES:

PHYSICAL FORM.....: Liquid APPEARANCE....: Clear COLOR....: Colorless ODOR....: Vinegar pH ..... 2.5 BOILING POINT....: Approx. 212 F (100 C) MELTING/FREEZING POINT...: Not Established SOLUBILITY IN WATER .....: Soluble SPECIFIC GRAVITY .....: 1.05 BULK DENSITY.....: Not Applicable VAPOR PRESSURE .....: Not Established

# 10. STABILITY AND REACTIVITY:

STABILITY...... This is a stable material. HAZARDOUS POLYMERIZATION...: Will not occur. INCOMPATIBILITIES...... Strong alkali, oxidizers INSTABILITY CONDITIONS....: None known. DECOMPOSITION PRODUCTS.....: Oxides of sulfur, CO2, carbon monoxide

#### 11. TOXICOLOGICAL INFORMATION:

TOXICITY DATA FOR: Acetic Acid ACUTE TOXICITY ORAL LD50.....: 3310 mg/kg (rat) DERMAL LD50....: 1060 mg/kg (rabbit) (1) INHALATION LC50...: LC50: 5620 ppm/1 hr. (mouse) (2) EYE EFFECTS.....: Corrosive SKIN EFFECTS.....: Corrosive

1 Supplier Material Safety Data Sheet 2 Occupational Health Services Material Safety Data Sheet

#### 12. ECOLOGICAL INFORMATION:

NO ECOLOGICAL INFORMATION AVAILABLE

#### 13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD.....: Recover nonusable free liquid and/or contaminated water, and dispose of in an approved and permitted treatment system. Remove nonusable solid material and/or contaminated soil, for disposal in an approved and permitted landfill. Discharge to sewer may require approval of permitting authority and may require pretreatment.

#### 14. TRANSPORTATION INFORMATION:

TECHNICAL SHIPPING NAME.....: Aqueous Photochemical Solution containing Acetic Acid and Aluminum Sulfate PRODUCT LABEL..... G-353C Fixer Part B DOT (DOMESTIC SURFACE) -----HAZARD CLASS OR DIVISION .....: Non-Regulated IMO / IMDG CODE (OCEAN) \_\_\_\_\_ HAZARD CLASS DIVISION NUMBER...: Non-Regulated ICAO / IATA (AIR) \_\_\_\_\_ HAZARD CLASS DIVISION NUMBER...: Non-Regulated 15. **REGULATORY INFORMATION:** OSHA STATUS..... : This product is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. TSCA STATUS...... On TSCA Inventory CERCLA REPORTABLE QUANTITY ..: Acetic Acid (CAS# 64-19-7) - 5,000 lbs.; Aluminum Sulfate (CAS# 10043-01-3) - 5,000 lbs. SARA TITLE III: SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES..: None SECTION 311/312 HAZARD CATEGORIES.....: Immediate Health Hazard SECTION 313 TOXIC CHEMICALS.....: None RCRA STATUS...... If discarded in its purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. (40 CFR 261.20-24) The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

COMPONENT NAME /CAS NUMBER	CONCENTRATION	STATE CODE
Acetic Acid		
64-19-7	1-5 %	PA1, PA4, MA, NJ1, NJ3
Aluminum Sulfate		
10043-01-3	1-5 %	PA1, PA4, MA, NJ1
Water		
7732-18-5	90-95 %	PA3, NJ4
Nonylphenol polyethylene oxide		
9016-45-9	1-5 %	PA3, NJ4

MA = Massachusetts Hazardous Substance List

NJ1 = New Jersey Hazardous Substance List NJ3 = New Jersey Special Health Hazardous Substance List NJ4 = New Jersey Other - included in 5 predominant ingredients > 1% PA1 = Pennsylvania Hazardous Substance List PA3 = Pennsylvania Non-hazardous present at 3% or greater. PA4 = Pennsylvania Environmental Hazardous Substance List.

# 16. OTHER INFORMATION:

HMIS RATINGS: Health Flammability Reactivity Personal Prot 2 0 0 B 0=Minimal 1=Slight 2=Moderate 3=Serious 4=Severe B=Safety Glasses, Gloves

Agfa's method of hazard communication is comprised of Product Labels and Material Safety Data Sheets. HMIS ratings are provided by Agfa as a customer service.

REASON FOR ISSUE.....: Reviewed, Harmonized PREPARED BY..... R. Ruppel-Kerr APPROVED BY..... M. Patrick APPROVAL DATE..... 06/12/2002 SUPERSEDES DATE..... 07/15/1998 MSDS NUMBER..... 34522

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Agfa Corporation. The data on this sheet relates only to the specific material designated herein. Agfa Corporation assumes no legal responsibility for use or reliance upon these data.

# THIS PAGE INTENTIALLY LEFT BLANK