



MATERIAL SAFETY DATA SHEET

Page: 2

E-Z-Cat Dry Product

Appearance & Odor: White to off-white powder with a slightly fruity or sweet odor.

---

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

---

Flash Point (method): N/A                      Flammable Limits: UEL - N/A      LEL - N/A

Fire Extinguishing Media: Use extinguishing media that is suitable for surrounding fire.

Special Fire Fighting Procedures: Firefighters should wear full protective equipment and self-contained breathing apparatus with full face piece.

Unusual Fire & Explosion Hazards: None known

Toxic Gases Emitted: sulfur dioxide, carbon dioxide, carbon monoxide.

---

SECTION V - REACTIVITY DATA

---

Stability: Stable                                      Conditions to avoid: None documented

Incompatible materials: Phosphorous, Aluminum, acids, bases, and oxidizers

Decomposition products: Not tested      Hazardous Polymerization: Will not occur

---

SECTION VI - HEALTH HAZARD DATA

---

Permissible Exposure Limit (PEL) for barium sulfate and nuisance dust.

Total Dust - 15 mg/m<sup>3</sup> Time Weighted Average (TWA)  
Respirable dust - 5 mg/m<sup>3</sup> TWA

Threshold Limit Value (TLV) for barium sulfate and nuisance dust:

Total Dust: 10 mg/m<sup>3</sup> TWA  
Silica - Quartz, Respirable: 0.1 mg/m<sup>3</sup>

F-527K

## E-Z-Cat Dry Product

---

**SECTION VI - HEALTH HAZARD DATA contd.**

---

Short-Term Exposure Limit (STEL): Not Established

Routes of Exposure: Inhalation, Ingestion

Health Hazards (acute and chronic): Through normal routes of entry, not expected to be a hazard.

May cause irritation to eyes, skin and lungs. No adverse health effects expected from chronic exposure.

Carcinogenicity: Crystalline silica is listed by IARC as a Class 2A carcinogen based on limited evidence in humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a substance reasonably anticipated to be a carcinogen.

NTP: Yes IARC: Yes OSHA: No

Sodium saccharin is listed by the NTP as a substance reasonably anticipated to be a carcinogen.

NTP: Yes IARC: No OSHA: No

Effects of exposure: Sorbitol may cause diarrhea in some individuals. No other effects are expected when used as directed. May cause irritation to eyes, skin and lungs.

Medical conditions generally aggravated by exposure: None known if used as directed.

Emergency and First Aid procedures: Eye contact - Flush with water for at least 15 minutes.

Skin contact - wash area thoroughly with soap and water.

If ingested and person is conscious - give several glasses of water to dilute. If irritation persists or large quantities are ingested, get medical attention.

---

**SECTION VII - SPILL AND DISPOSAL INFORMATION**

---

Steps to be taken in case material is released or spilled:

Wear appropriate protective equipment; safety goggles and gloves. Sweep material up

MATERIAL SAFETY DATA SHEET

Page: 4

E-Z-Cat Dry Product

(minimize the amount of dust). Place materials in container and label properly.

Waste Disposal Procedures:

Products are not listed hazardous wastes under RCRA. Products are not likely to qualify as characteristic hazardous wastes, but any final determination depends on the specific circumstances of product usage and handling. Disposal should take place in compliance with federal, state and local laws and regulations.

---

SECTION VIII - HANDLING AND STORAGE PRECAUTIONS

---

Store in a cool, dry temperature (50-70 degrees F). Avoid unnecessary skin contact and inhalation.

Do not smoke, eat or drink while handling any chemical. Practice good industrial and personal hygiene to avoid unnecessary exposure.

---

SECTION IX - PROTECTIVE EQUIPMENT

---

Respiratory Protection: If exposure limits are exceeded use a dust respirator.

Ventilation: Use adequate local exhaust ventilation to keep dust levels as low as possible.

Protective Gloves: Appropriate gloves.

Eye Protection: Safety goggles or glasses.

Emergency Equipment: Always ensure there is an emergency eye wash in the area.

Disclaimer: The information contained in this Material Safety Data Sheet is believed to be correct, but does not purport to be all inclusive, and should only be used as a guide. E-Z-EM Inc. and subsidiaries shall not be held liable for any damage resulting from the handling or contact with these products.

This is an electronic document. Any alteration to the original renders this document invalid. The holder shall be held liable for any alterations made to this document.

F-527K

MATERIAL SAFETY DATA SHEET

Page: 5

E-Z-Cat Dry Product

F-527K