

Material Safety Data Sheet

Revision Date: 10/09/2007
Z17000000755/Version: 1.3
Print Date: 01/26/2009
Page: 1/7



1. Identification of the substance/preparation and of the company/undertaking

Product name: KODAK Indicator Stop Bath

Product code: 1464247

Supplier: EASTMAN KODAK COMPANY, 343 State Street, Rochester, New York, 14650

For Emergency Health, Safety & Environmental Information, call (585) 722-5151 (USA)

For other information or to request an MSDS, call (800) 242-2424.

Synonyms: PCD 2838

Product Use: photographic processing chemical, For consumer and industrial use.

2. Hazards identification

CONTAINS: Acetic acid (64-19-7)

DANGER!

POISON

MAY BE FATAL OR HARMFUL IF SWALLOWED

DUST, MIST OR VAPOUR EXTREMELY IRRITATING TO THE EYES AND RESPIRATORY TRACT

CAUSES SEVERE SKIN AND EYE BURNS

COMBUSTIBLE LIQUID AND VAPOR

NFPA Hazard Ratings: Health - 3, Flammability - 2, Instability - 0

NOTE: NFPA 704 (2007) hazard indexes involves data review and interpretation that may vary among companies. It is intended only for rapid, general identification of the magnitude of the potential hazards. To adequately address safe handling, ALL information in this MSDS must be considered.

3. Composition/information on ingredients

Weight %	Components - (CAS-No.)
85 - 90	Acetic acid (64-19-7)

4. First aid measures

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration using mouth guards or shields, when available, to avoid mouth-to-mouth contact. If breathing is difficult, give oxygen. Get medical attention.

Eyes: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Material Safety Data Sheet



Revision Date: 10/09/2007
Z17000000755/Version: 1.3
Print Date: 01/26/2009
Page: 2/7

Skin: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician or poison control centre immediately. Wash contaminated clothing before re-use. Destroy or thoroughly clean contaminated shoes.

Ingestion: If swallowed, do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control centre immediately.

5. Fire-fighting measures

Extinguishing Media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Use water spray to cool unopened containers.

Hazardous Combustion Products: Carbon oxides

Unusual Fire and Explosion Hazards: Combustible. Material contains a combustible solvent that may accumulate in the container headspace.

6. Accidental release measures

Remove all sources of ignition. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination.

7. Handling and storage

Personal precautions: Do not breathe vapour at concentrations greater than the exposure limits. Do not get in eyes, on skin, or on clothing. Keep container tightly closed. Use only with adequate ventilation. Wash thoroughly after handling.

Prevention of Fire and Explosion: Keep away from heat and sources of ignition. Ensure adequate ventilation. Keep from contact with oxidizing materials.

Storage: Keep container tightly closed. Keep away from incompatible substances (see Incompatibility section.)

8. Exposure controls / personal protection

Occupational exposure controls

Chemical Name	Regulatory List	Value Type	Value
Acetic acid	ACGIH	time weighted average	10 ppm
	ACGIH	Short term exposure limit	15 ppm
	OSHA Z1	time weighted average	10 ppm 25 mg/m3
	OSHA Z1A	time weighted average	10 ppm 25 mg/m3

Ventilation: Use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. Controls should be sufficient so that applicable occupational exposure limits are not exceeded.

Material Safety Data Sheet

Revision Date: 10/09/2007
Z17000000755/Version: 1.3
Print Date: 01/26/2009
Page: 3/7



Respiratory protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits, an approved respirator must be worn. Respirator type: full-face organic vapour cartridge. If respirators are used, a program should be instituted to assure compliance with applicable federal, state, commonwealth, provincial, or local laws and regulations.

Eye protection: If a full-face respirator is not worn, wear vapour-tight chemical goggle and a face shield.

Hand protection: Wear impervious gloves and protective clothing appropriate for the risk of exposure.

9. Physical and chemical properties

Physical form: liquid

Colour: light yellow

Odour: sharp vinegar

Specific gravity: 1.07

Vapour pressure: 19.5 mbar (14.6 mm Hg)

Vapour density: 1.9

Volatile fraction by weight: 100 %

Boiling point/boilingrange: 100.0 °C (212.0 °F)

Water solubility: complete

pH: 2

Flash point: 53.3 °C (127.9 °F)

10. Stability and reactivity

Stability: Stable under normal conditions.

Incompatibility: Strong oxidizing agents, Bases, Amines, Metals.

Hazardous decomposition products: None under normal conditions of use.

Hazardous Polymerization: Hazardous polymerisation does not occur.

11. Toxicological information

Effects of Exposure

General advice:

Contains: Acetic acid. Acute overexposure to extremely high airborne concentrations of

Material Safety Data Sheet

Revision Date: 10/09/2007
Z17000000755/Version: 1.3
Print Date: 01/26/2009
Page: 4/7



respiratory irritants has been associated with development of an asthma-like reactive airways syndrome (RADS) in susceptible individuals. Extremely high airborne concentrations are not generated during normal conditions of use but may occur following a spill. The potential to generate extremely high airborne concentrations in a spill situation depends upon physical factors such as the concentration of the solution, the volume of the spill, the surface area of the spill, the size of the room where the spill occurred, and the ventilation rate in the room.

Inhalation: Airborne dust/mist/vapor extremely irritating.

Eyes: Causes severe eye burns. Airborne dust/mist/vapor extremely irritating.

Skin: Causes severe skin burns.

Ingestion: May be fatal or harmful if swallowed. May cause burns of the gastrointestinal tract if swallowed.

Data for Acetic acid (CAS 64-19-7):

Acute Toxicity Data:

- Oral LD50 (rat): 3,310 - 3,530 mg/kg
- Oral LD50: 4,960 mg/kg
- Inhalation LC50: 5620 ppm / 1.00 hr
- Dermal LD50: 1,060 mg/kg
- Skin irritation: severe
- Eye irritation: severe
- Eye irritation (washed eyes): severe
- Eye irritation (unwashed eyes): severe

12. Ecological information

The following properties are ESTIMATED from the components of the preparations.

Potential Toxicity:

Toxicity to fish (LC50):	10 - 100 mg/l
Toxicity to daphnia (EC50):	10 - 100 mg/l
Toxicity to algae (IC50):	> 100 mg/l
Toxicity to other organisms (EC50):	> 100 mg/l

Persistence and degradability: Readily biodegradable.

Chemical Oxygen Demand (COD): 940 g/l

Biochemical Oxygen Demand (BOD): 680 g/l

13. Disposal considerations

Material Safety Data Sheet



Revision Date: 10/09/2007
Z17000000755/Version: 1.3
Print Date: 01/26/2009
Page: 5/7

Discharge, treatment, or disposal may be subject to federal, state, commonwealth, provincial, or local laws. Since emptied containers retain product residue, follow label warnings even after container is emptied.

14. Transport information

The information given below is provided to assist in documentation. It may supplement the information on the package. The package in your possession may carry a different version of the label depending on the date of manufacture. Depending on inner packaging quantities and packaging instructions, it may be subject to specific regulatory exceptions. Please consult the product packaging for further details.

IATA:	UN Number:	UN2789
	Proper shipping name:	Acetic acid solution
	Class:	8
	Sub-risks:	3
	Packaging group:	II
IMDG:	UN Number:	UN2789
	Proper shipping name:	ACETIC ACID SOLUTION
	Class:	8
	Sub-risks:	3
	Packaging group:	II
US DOT:	UN Number:	UN2789
	Proper shipping name:	Acetic acid solution
	Class:	8
	Sub-risks:	3
	Packaging group:	II

For more transportation information, go to: www.kodak.com/go/ship.

15. Regulatory information

Notification status

Regulatory List	Notification status
EINECS	y (positive listing)
TSCA	y (positive listing)
AICS	y (positive listing)
DSL	y (positive listing)
ENCS (JP)	y (positive listing)
KECI (KR)	n (Negative listing)
PICCS (PH)	y (positive listing)
INV (CN)	y (positive listing)

A N (Negative listing) indicates one or more component is either not on the public Inventory or is subject to exemption requirements. If additional information is needed contact Kodak.

Material Safety Data Sheet



Revision Date: 10/09/2007
Z17000000755/Version: 1.3
Print Date: 01/26/2009
Page: 6/7

Other regulations

American Conference of Governmental Industrial Hygienists (ACGIH):	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
International Agency for Research on Cancer (IARC):	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
U.S. National Toxicology Program (NTP):	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
U.S. Occupational Safety and Health Administration (OSHA):	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
California Prop. 65:	none
US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323):	Acetic acid, Water
US. Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000):	No components are subject to the Massachusetts Right to Know Act.
US. New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5):	Acetic acid, Water
US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required:	SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A):	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

16. Other information

The data below reflects current legislative requirements whereas the product in your possession may carry a different version of the label depending on the date of manufacture.

US/Canadian Label Statements:

CONTAINS: Acetic acid (64-19-7)

**DANGER!
POISON
MAY BE FATAL OR HARMFUL IF SWALLOWED**

Material Safety Data Sheet

Revision Date: 10/09/2007
Z17000000755/Version: 1.3
Print Date: 01/26/2009
Page: 7/7



**DUST, MIST OR VAPOUR EXTREMELY IRRITATING TO THE EYES AND RESPIRATORY TRACT
CAUSES SEVERE SKIN AND EYE BURNS
COMBUSTIBLE LIQUID AND VAPOR**

Do not breathe vapours or spray mist.
Do not get in eyes, on skin, or on clothing.
Keep container tightly closed.
Use only with adequate ventilation.
Wash thoroughly after handling.

FIRST AID: If inhaled, remove to fresh air. If not breathing, give artificial respiration using mouth guards or shields, when available, to avoid mouth-to-mouth contact. If breathing is difficult, give oxygen. Get medical attention. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician or poison control centre immediately. Wash contaminated clothing before re-use. Destroy or thoroughly clean contaminated shoes. If swallowed, do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control centre immediately.

Keep out of reach of children.

Do not handle or use until safety precautions in Material Safety Data Sheet (MSDS) have been read and understood.

Since emptied containers retain product residue, follow label warnings even after container is emptied.

IN CASE OF FIRE: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

IN CASE OF SPILL: Remove all sources of ignition. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination.

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment. The information relating to the working solution is for guidance purposes only, and is based on correct mixing and use of the product according to instructions.

R-2, S-3, F-2, C-0